

Typical performance/典型性能

- ◆ 特点: 定电压输入, 隔离稳压输出, 1W 功率
Characteristics: Fixed Input, Isolation, Regulated Output, 1W
- ◆ 隔离电压 Isolation voltage: 1000VDC/3000VDC
- ◆ 效率 Efficiency : 高达(up to) 72%
- ◆ 工作环境温度 Working temperature : -40°C ~ +85°C
- ◆ MTBF ≥ 350 万小时(350000Hrs)
- ◆ 符合 RoHS 指令 In line with RoHS codes
- ◆ 线性调节率 (输入电压变化 ±5%) ±0.25%
Line regulation (once input change ±5%) ±0.25%
- ◆ 负载调节率(10%-100%满载) ±1% Load regulation (10%-100% full load) ±1%
- ◆ 纹波/ 噪声(20MHz 带宽) < 100mVp-p
Ripple and noise (20MHz Band width) < 100mVp-p
- ◆ 可持续短路保护 Constant short circuit protection



典型产品列表 Typical product tabulates

型号 TYPE	输入电压范围 Input voltage range	标称输出电压/输出电流 (Nominal output voltage / output current)					
		VO1			VO2		
		电压 (V) Input voltage	最小电流 Min mA	最大电流 Max mA	电压 (V) Input voltage	最小电流 Min mA	最大电流 Max mA
NW1-□S05S	5V (4.75~5.25VDC)	5V	20mA	200mA			
NW1-□S09S	12V (11.4~12.6VDC)	9V	11mA	110mA			
NW1-□S12S	24V (22.8~25.2VDC)	12V	8.3mA	83mA			
NW1-□S15S	48V (45.6~50.4VDC)	15V	6.8mA	68mA			
NW1-□S24S		24V	4.2mA	42mA			
NW1-□D05S		+5V	10mA	100mA	-5V	10mA	100mA
NW1-□D09S		+9V	5.5mA	55mA	-9V	5.5mA	55mA
NW1-□D12S		+12V	4mA	40mA	-12V	4mA	40mA
NW1-□D15S		+15V	3.3mA	33mA	-15V	3.3mA	33mA
NW1-□D24S		+24V	2.1mA	21mA	-24V	2.1mA	21mA
NW1-□D05IS		+5V	10mA	100mA	+5V	10mA	100mA
NW1-□D09IS		+9V	5.5mA	55mA	+9V	5.5mA	55mA
NW1-□D12IS		+12V	4mA	40mA	+12V	4mA	40mA
NW1-□D15IS		+15V	3.3mA	33mA	+15V	3.3mA	33mA
NW1-□D24IS		+24V	2.1mA	21mA	+24V	2.1mA	21mA

NW1-□S05S3	5V	20mA	200mA			
NW1-□S09S3	9V	11mA	110mA			
NW1-□S12S3	12V	8.3mA	83mA			
NW1-□S15S3	15V	6.8mA	68mA			
NW1-□S24S3	24V	4.2mA	42mA			
NW1-□D05S3	+5V	10mA	100mA	-5V	10mA	100mA
NW1-□D09S3	+9V	5.5mA	55mA	-9V	5.5mA	55mA
NW1-□D12S3	+12V	4mA	40mA	-12V	4mA	40mA
NW1-□D15S3	+15V	3.3mA	33mA	-15V	3.3mA	33mA
NW1-□D24S3	+24V	2.1mA	21mA	-24V	2.1mA	21mA

注：□代表输入电压标称值，因篇幅有限，以上只是部分产品列表，若需列表以外产品，请与本公司销售部联系。

□Shows the nominal value of input voltage, due to space limitations, the above list is only for some products, if other than a list of products, please contact the Company's sales department.

封装尺寸 Mechanical Data

封装代号 Package code	L x W x H	
A (单路输出 single output)	19.50 × 6.00 × 10.00mm	0.76 × 0.23 × 0.39inch
B (两路正负输出 dual output)	27.50 × 9.50 × 12.00mm	1.08 × 0.37 × 0.47inch
C (两路隔离输出 dual output isolated)	27.50 × 9.50 × 12.00mm	1.08 × 0.37 × 0.47inch
D (单路输出 3000VDC 隔离 single output 3000VDC isolated)	19.50 × 6.00 × 10.00mm	0.76 × 0.23 × 0.39inch
E (两路正负输出 3000VDC 隔离 dual output 3000VDC isolated)	27.50 × 9.50 × 12.00mm	1.08 × 0.37 × 0.47inch


封装尺寸图 Mechanical Data

■ 封装尺寸 A: 单路输出 (single route output)SIP

管脚代码	1	2	3	4	5	6	7
功能(Usage)	Vin	GND		-Vo1		+Vo1	

▲注: 所有单位尺寸为 mm, 所有相邻端子间距为 2.54mm, 所有端子直径为 0.65mm

▲Note:Aaa unit is mm,all neighboring pin distance is 2.54mm,all ping diameter is 0.65mm.




■ 封装尺寸 B: 正负两路输出 (Duel route Positive and negative out)SIP

管脚代码	1	2	3	4	7	9	10
功能(Usage)	Vin	GND			+Vo	-Vo	COM

▲注: 所有单位尺寸为 mm, 所有相邻端子间距为 2.54mm, 所有端子直径为 0.65mm

▲Note:Aaa unit is mm,all neighboring pin distance is 2.54mm,all ping diameter is 0.65mm.




■ 封装尺寸 C: 两路隔离输出 (Duel route isolation output)SIP

管脚代码	1	2	3	7	8	9	10
功能(Usage)	Vin	GND		+Vo1	-Vo1	-Vo2	+Vo2

▲注: 所有单位尺寸为 mm, 所有相邻端子间距为 2.54mm, 所有端子直径为 0.65mm

▲Note:Aaa unit is mm,all neighboring pin distance is 2.54mm,all ping diameter is 0.65mm.




■ 封装尺寸 D: 单路输出 3000VDC 隔离 (Single route output 3000VDC)SIP

管脚代码	1	2	3	4	5	6	7
功能(Usage)	Vin	GND		-Vo		+Vo	

▲注: 所有单位尺寸为 mm, 所有相邻端子间距为 2.54mm, 所有端子直径为 0.65mm

▲Note:Aaa unit is mm,all neighboring pin distance is 2.54mm,all ping diameter is 0.65mm.



■ 封装尺寸 E: 两路正负输出 3000VDC 隔离(Duel route Posivlve and negative out 3000VD)SIP

管脚代码	1	2	3	4	7	9	10
功能(Usage)	Vin	GND			+Vo	-Vo	COM

▲注: 所有单位尺寸为 mm, 所有相邻端子间距为 2.54mm, 所有端子直径为 0.65mm

▲Note:Aaa unit is mm,all neighboring pin distance is 2.54mm,all ping diameter is 0.65mm.

